


DMW-螺紋陰井(WSO)-規格表



螺紋滲透陰井同徑平接頭規格表

標稱管徑		內徑*外徑 ±3.0%mm	螺距 ±3.0%mm	長度 m
英吋	型號			
6"	WSO-150A	148*165	14.0mm	5m
8"	WSO-200A	195*216	14.5mm	5m
10"	WSO-250A	239*267	14.5mm	5m
12"	WSO-300A	290*318	15.0mm	5m
16"	WSO-400A	390*420	15.5mm	5m

標稱管徑		內徑*外徑 ±3.0%mm	螺距 ±3.0%mm	長度 cm
型號	型號			
6"F	WSF-150A	166.0x183.0	14.5mm	25cm
8"F	WSF-200A	217.0*240.0	14.5mm	30cm
10"F	WSF-250A	268.0*290.0	14.5mm	35cm
12"F	WSF-300A	320.0*342.0	15.0mm	40cm
16"F	WSF-400A	422.0*452.0	15.5mm	45cm



DMW-螺紋陰井-獨有特性

→ 管壁高密度網孔設計

→ 管壁T型螺紋環繞，抗壓性高

→ DMW-螺紋陰井防沙土進入管內的結構設計，管壁不需不織布等過濾材料，網管抗阻塞。

